

Specification for TT 12

Issued on: 25-Apr-08

Issued on: 5-Mar-10

1. Spec

Style #	TT-12	
LED	Color Options	Red, Green, Amber or White
	Grade	Super Intensity
	LED Type	Oval shape(4.0*5.0mm)
	Viewing angle	140°(Hori.) / 30°(Ver.)
Set	Display(screen) size(mm)	11"H x 25.25"W (279.4mmH x 641.4mmW)
	Total(case) size(mm)	13"H x 27.25"W (330.2mmH x 692.2mmW)
	Display Weight	15lbs (6.8kg)
	Power (Output Voltage)	120 VAC / 240 VAC (Available)
	Character Heights	12 inches
	Viewing Distance	9ft - 246ft (3m - 75m)
	Operating Temp.	-40°C ~ 50°C / -40°F ~ 120°F
	Operation	Wireless Remote Control Terminal (1Km line of sight) USB Wireless Software (Optional)
	Casing	100mm Aluminum case
	Warranty	1 year

2. Features:

1. Designed for outdoor (water tight design)



598 Patterson Blvd., Pleasant Hill, Ca USA

Tel: 800-660-4414 Fax: 925-939-9998 E-mail: info@sunriseled.us

Specification for TT 16

Issued on: 25-Apr-08

Issued on: 5-Mar-10

1. Spec

Style #	TT-16	
<u>LED</u>	Color Options	Red, Green, Amber or White
	Grade	Super Intensity
	LED Type	Oval shape(4.0*5.0mm)
	Viewing angle	140°(Hori.) / 30°(Ver.)
<u>Set</u>	Display(screen) size(mm)	15"H x 37"W (381mmH x 939.8mmW)
	Total(case) size(mm)	17"H x 39"W (431.8mmH x 990.6mmW)
	Display Weight	25lbs (11.3kg)
	Power (Output Voltage)	120 VAC / 240 VAC (Available)
	Character Heights	16 inches
	Viewing Distance	19ft - 492ft (6m - 150m)
	Operating Temp.	-40°C ~ 50°C / -40°F ~ 120°F
	Operation	Wireless Remote Control Terminal (1Km line of sight) USB Wireless Software (Optional)
	Casing	100mm Aluminum case
	Warranty	1 year

2. Features:

1. Designed for outdoor (water tight design)



598 Patterson Blvd., Pleasant Hill, Ca USA

Tel: 800-660-4414 Fax: 925-939-9998 E-mail: info@sunriseled.us

Specification for TT 20

Issued on: 25-Apr-08

Issued on: 5-Mar-10

1. Spec

Style #	TT-20	
<u>LED</u>	Color Options	Red, Green, Amber or White
	Grade	Super Intensity
	LED Type	Oval shape(4.0*5.0mm)
	Viewing angle	140°(Hori.) / 30°(Ver.)
<u>Set</u>	Display(screen) size(mm)	20"H x 48.5"W (508mmH x 1231.9mmW)
	Total(case) size(mm)	22"H x50.5"W (558.8mmH x 1282.7mmW)
	Display Weight	35lbs (16kg)
	Power (Output Voltage)	120 VAC / 240 VAC (Available)
	Character Heights	20 inches
	Viewing Distance	38ft - 984ft (12m - 300m)
	Operating Temp.	-40°C ~ 50°C / -40°F ~ 120°F
	Operation	Wireless Remote Control Terminal (1Km line of sight) USB Wireless Software (Optional)
	Casing	100mm Aluminum case
	Warranty	1 year

2. Features:

1. Designed for outdoor (water tight design)



598 Patterson Blvd., Pleasant Hill, Ca USA

Tel: 800-660-4414 Fax: 925-939-9998 E-mail: info@sunriseled.us

Specification for TT 24

Issued on: 25-Apr-08

Issued on: 5-Mar-10

1. Spec

Style #	TT-24	
<u>LED</u>	Color Options	Red, Green, Amber or White
	Grade	Super Intensity
	LED Type	Oval shape(4.0*5.0mm)
	Viewing angle	140°(Hori.) / 30°(Ver.)
<u>Set</u>	Display(screen) size(mm)	23"H x 55"W (609.6mmH x 1397mmW)
	Total(case) size(mm)	26"H x 57"W (660.4mmH x 1447.8mmW)
	Display Weight	45lbs (20.4kg)
	Power (Output Voltage)	120 VAC / 240 VAC (Available)
	Character Heights	24 inches
	Viewing Distance	38ft - 984ft (12m - 300m)
	Operating Temp.	-40°C ~ 50°C / -40°F ~ 120°F
	Operation	Wireless Remote Control Terminal (1Km line of sight) USB Wireless Software (Optional)
	Casing	100mm Aluminum case
	Warranty	1 year

2. Features:

1. Designed for outdoor (water tight design)