



598 Patterson Blvd., Pleasant Hill, CA USA
 Tel: 800-660-4414 Fax: 925-939-9998 E-mail: info@sunriseled.us

Specification for Flood Light 12W

Issued on: 1/4/2008

Revised on: 3/10/2010

1. Specs

Optical Specs	Warm White	Cool White
LED Efficiency	>60.9Lm/W	>87Lm/W
Drivers	External listed waterproof power supply	
Luminous Flux	>#Lm	
LED Colors	RGB (4 Red, 4 Green, 4 Blue) AWB (4 Amber, 4 White, 4 Blue) Wht (12 White)	
Beam Angle	60° / 30°	
Electrical Specs		
Input Voltage & Frequency	AC100-240V 50-60Hz	
Max Power Consumption	14W	
Energy Consumption Per Year	#Kw/Hr	
Operating Current		
Light Source	#W	
Control Mode	DMX 512 Console	
Other Specs		
Operating Temperature	-30°C - +45°C (-22°F - +113°F)	
Operating Humidity	10 - 90 RH	
Storage Temperature	-20°C - +45°C (-4°F - +113°F)	
Dimensions	4.4"H x 2.75"W x 16.3"L (112mmH x 70mmW x 415mmL)	
Fabrication Material	Aluminum Alloy & Glass	
Net Weight	1.8±0.4lbs (1.8±0.2kg)	
Lifespan	50,000 Hours	
Warranty	3 Years	