



598 Patterson Blvd., Pleasant Hill, CA USA

Tel: 800-660-4414 Fax: 925-939-9998 E-mail: info@sunriseled.us

## Specification for Flood Light 180W

Issued on: 1/4/2008

Revised on: 3/10/2010

### 1. Specs

Optical Specs	Warm White	Cool White
LED Efficiency	>60.9Lm/W	>87Lm/W
Drivers	External listed waterproof power supply	
LED Colors	RGB (12 Red, 12 Green, 12 Blue) * 2.4W AWB (12 Amber, 12 White, 12 Blue) * 2.4W Wht (36 White) * 2.4W	
Beam Angle	60° / 30°	
<b>Electrical Specs</b>		
Input Voltage & Frequency	DC24V   50-60Hz	
Max Power Consumption	176W	
Control Mode	DMX 512 Console	
<b>Other Specs</b>		
Operating Temperature	-30°C - +45°C (-22°F - +113°F)	
Operating Humidity	10 - 90 RH	
Storage Temperature	-20°C - +45°C (-4°F - +113°F)	
Dimensions	5.8"H x 7.7"W x 48"L (148mmH x 196mmW x 1220mmL)	
Fabrication Material	Aluminum Alloy & Glass	
Net Weight	9.5±1.1lbs (9.5±0.5kg)	
Lifespan	50,000 Hours	
Warranty	3 Years	