



598 Patterson Blvd., Pleasant Hill, CA USA

Tel: 800-660-4414 Fax: 925-939-9998 E-mail: info@sunriseled.us

Specification for Flood Light 72W

Issued on: 1/4/2008

Revised on: 3/10/2010

1. Specs

Optical Specs	Warm White	Cool White
LED Efficiency	>60.9Lm/W	>87Lm/W
Drivers	External listed waterproof power supply	
LED Colors	RGB (24 Red, 24 Green, 24 Blue) AWB (24 Amber, 24 White, 24 Blue) Wht (72 White)	
Beam Angle	60° / 30°	
Electrical Specs		
Input Voltage & Frequency	DC24V 50-60Hz	
Max Power Consumption	85W	
Control Mode	DMX 512 Console	
Other Specs		
Operating Temperature	-30°C - +45°C (-22°F - +113°F)	
Operating Humidity	10 - 90 RH	
Storage Temperature	-20°C - +45°C (-4°F - +113°F)	
Dimensions	5.8"H x 7.7"W x 47.3"L (148mmH x 196mmW x 1202mmL)	
Fabrication Material	Aluminum Alloy & Glass	
Net Weight	9.2±1.1lbs (9.2±0.5kg)	
Lifespan	50,000 Hours	
Warranty	3 Years	